










KINDS&APPLICATIONS OF “U”PIG

Shape & Name	Type Name	Remarks	Application Example
 Swab	“U” PIG SW	Hardness 1	Wiping OFF water and oil
 Soft Bare	“U” PIG SB	Hardness 2	Wiping OFF water and oil from a large quantity of sludge deposited line
 Bare	“U” PIG GB	Hardness 15	For guide of new piping arrangement and for various lines ※
	“U” PIG RB	Hardness 25	
	“U” PIG BB	Hardness 45	Industrial water and city water lines
 Mole	“U” PIG M3 M9	Hardness 60	Sludge, gas-line and oil-line ※
		Hardness 80	Calcium group and silica
		Hardness 90	Sea-water line
 Ball	“U” PIG B2	Hardness 20	For purging
	“U” PIG B8	Hardness 80	For lining
 Wire-Brush	“U” PIG GW	One-piece structure of Wire-Brush on Bare surfaces	Newly arranged piping line ※
	“U” PIG RW		Bonding agent line and gas-line ※
	“U” PIG BW		Heating furnace
 Hard-Claw	“U” PIG H6	M6 + Pin	Industrial water and city water lines Rust sludge and sea-water line ※
	“U” PIG H8	M8 + Pin	Calcium gr. scale and cement slurry
	“U” PIG H9	M9 + Pin	Heating furnace (Hard C, iron sulfide)
 Coated	“U” PIG GC	Coated with full urethane elastomer on bare surfaces	Solvent group Naphtha LPG, LNG Cleaning for a plenty of rust lines For purging ※
	“U” PIG RC		
	“U” PIG BC		
 Displacement	“U” PIG DP	Solvent-proof	For purging For oil change Solvent group

■ Sizes up to 1” (25mm) ~ 12” (300mm) are stocked and available.(Marked with *)
 Port sizes more than 14” can be fabricated up to φ 3M on order.(Delivery period: 20days)